



Tubo in mescola termoplastica a base PVC,PU,GOMMA NITRILICA a due strati con spirale in acciaio zincato incorporata e rinforzo in fibra poliestere, per aspirazione e mandata olii, blue diesel, diesel e bio diesel.

Two-layer hose in thermoplastic PVC, PU, NITRILE RUBBER compound with embedded galvanised steel spiral with polyester yarn reinforcement for suction and delivery of oils, blue diesel, diesel, bio diesel.



SUPERFICI LISCE
SMOOTH SURFACE



FLESSIBILITÀ
FLEXIBILITY



RESISTENZA ALL'ABRASIONE
ABRASION RESISTANCE

ISO 4649:<90 mm³



TEMPERATURA D'IMPIEGO
TEMPERATURE RANGE

-25° C + 55° C



RESISTENZA CHIMICA
CHEMICAL RESISTANCE

tabella PVC OIL



RESISTENZA ALLO SCHIACCIAMENTO
CRUSHING RESISTANCE

Tubo in mescola PVC-PU gomma nitrilica

Inner hose made of a PVC - PU and nitrile rubber compound

Spirale in acciaio

Steel spiral

Rinforzo in fibra poliestere

Poliester yarn reinforcement

Tubo in mescola PVC-PU gomma nitrilica

Outer cover made of a PVC - PU and nitrile rubber compound

Ø INTERNO Ø I.D.	Ø INTERNO Ø I.D.	Ø ESTERNO Ø O.D.	PESO WEIGHT	RAGGIO CURVATURA BENDING RADIUS	PRESS. ESERCIZIO WORKING PRESS.	PRESS. SCOPPIO BURSTING PRESS.	SOTTOVUOTO VACUUM	LUNG. ROTOLI COIL LENGTH
inc	mm	mm	g/m	mm	bar	bar	m H ₂ O	mt
3/4	19	28	450	70	16	48	9	60
1	25	35,5	640	80	16	48	9	60
1 1/4	32	42,5	800	100	16	48	9	60
	35	48	1050	120	14	42	9	60
1 1/2	38	51	1200	125	14	42	9	40
	40	53	1200	130	14	42	9	40
1 3/4	45	58	1340	140	12	36	9	40
2	50	64	1730	150	12	36	9	40
	60	74	1950	180	12	36	9	40
2 1/2	63	77	2030	190	12	36	9	40

